



EL-MR-WL

LOW PROFILE, WET LOCATION MR16 EMERGENCY LIGHT

PRODUCT OVERVIEW

The TES-EL-MR-WL wet location emergency light features a low profile design and is suitable for outdoor installations. Designed with durability and style in mind this vandal and impact resistant emergency lighting unit combines functionality with aesthetics. Ideal for commercial, retail and industrial facilities that require heavy duty protection emergency lighting in damp locations. The TES-EL-MR-WL series uses an injection molded UV stabilized shell and a thick polycarbonate thermoplastic housing and solid-state electronics to offer both reliability and low cost performance

EXTERNAL SPECIFICATIONS

Compact, low-profile design with a gray finish. Thick polycarbonate shell with injection molded, V-O flame retardant, high impact, thermoplastic housing.

INTERNAL SPECIFICATIONS

AC Only: Standard 120/277VAC input
Battery Backup: Standard self-powered versions use sealed 6v sealed lead acid batteries to provide a minimum 90 minutes of operation during an emergency where power is lost.

DIMENSIONS

5.7"h x 14.9"w x 4.2"d

INSTALLATION SPECIFICATIONS

The TES-EL-MR-WL luminaire is suitable for surface wall or ceiling mounting on normally inflammable surfaces. Suitable for outdoor, wet location environments where temperatures remain above 32°F. Operates using 120/277VAC.

CHARGER SPECIFICATIONS

A push button test switch allows maintenance personnel to quickly confirm the operational status of the emergency light.

CODE & STANDARDS COMPLIANCE

Certified to UL924 Standards for Canada and USA by Underwriters Laboratories.

HOW TO ORDER

Sample Order: TES-EL-MR-1-WL- BB (TES-EL-MR Series, Gray Housing, Wet Location, Battery Backup)

SERIES	HOUSING COLOR	WET LOCATION	OPTIONS
TES-EL-MR-WL	1 - Gray	WL - WL Rated	BB - Battery Backup