

Thermoplastic Exit

## ■ Indoor Architectural Exits

### PRODUCT OVERVIEW

The TES-ENDURA Series combines sturdiness and affordability to create an exceptionally value, only available through The Exit Store. If you like the price of thermoplastic signs but are looking for a more durable product, then the ENDURA Series is the right choice. Designed for indoor applications, the ENDURA Series housing is twice as thick as the TES-EXIT and TES-MES thermoplastic exit signs. This increase in thickness increases the ability of the product to withstand abuse and remain functional in institutional and commercial installations such as schools and shopping centers. The ENDURA Series uses high-output red or green LED technology. The ENDURA Series thermoplastic exit sign comes standard with two (2) EXIT stencils, one (1) backplate and a canopy. AC only and battery backup versions are available.



### EXTERNAL SPECIFICATIONS

The TES-ENDURA series is constructed from thick and durable corrosion and flame resistant thermoplastic. The TES-ENDURA series comes standard with a mounting canopy, two (2) EXIT stencils, one (1) backplate, removeable chevrons and all mounting hardware. The TES-ENDURA series comes standard finished in white; optional black finish is available. A damp location rating is standard on all TES-ENDURA series products. An external LED status indicator and test switch is standard on all self-powered models.

### ORDERING INFORMATION

DESCRIPTION: ENDURA, Red Letter, White Housing, Battery Backup

Series	Letter Color	Housing Color	Model
ENDURA	<input type="text"/>	<input type="text"/>	<input type="text"/>
	<ul style="list-style-type: none"> <li>• R (Red)</li> <li>• G (Green)</li> </ul>	<ul style="list-style-type: none"> <li>• W (White)</li> <li>• B (Black)</li> </ul>	<ul style="list-style-type: none"> <li>• AC (AC Only)</li> <li>• BB (Battery Backup)</li> </ul>

• EXAMPLE: ENDURA-R-W-BB



# ENDURA

Thermoplastic Exit

## MECHANICAL SPECIFICATIONS

Field removeable directional chevron arrows are standard. The TES-ENDURA series can be universally mounted and configured for single or double face applications. Canopy and mounting hardware are included. High-output LED technology provides energy savings, long life and even illumination levels. 120/277VAC input, maintenance free, sealed Nickel-Cadmium batteries are protected by an electronic cut-off circuit that prevents overdischarge. External test switch and monitor LED are standard on BB versions.

## BATTERY TECHNOLOGY

The TES-ENDURA series is designed with a maintenance free, sealed Nickel-Cadmium battery providing a minimum emergency duration of 90 minutes. Recharge time of the battery is twenty- four (24) hours. The maximum battery working temperature is 50 C.

## ELECTRICAL SPECIFICATIONS

The ENDURA series is configured with high-output LED lamps. LED is standard with 120/277VAC input. All LED versions consume only 1.1W nominal power.

## INSTALLATION

The TES-ENDURA series exit is suitable for surface ceiling, wall and end mounting. Suitable for indoor and damp location installations on normally inflammable surfaces.

## CODE AND STANDARDS COMPLIANCE

UL924 Listed.

